



EBTZ-42440-4ERR

NUMBER
OF ZONES

ELECTRONIC
LETTERING

TIME
COLOR

LOCATION
COLOR


SPECIFICATIONS

TYPE:	Alphanumeric in (RED-R GREEN-G YELLOW-Y BLUE-B) NOTE: BLUE IS SPECIAL ORDER.
DISPLAY:	4-DIGIT, 7 seg. RED LED and 15 CHARACTER DOT- MATRIX LED
CHARACTER HEIGHT:	4" TIME IN RED, GREEN or BLUE (101.6mm) Hr / Min 1.2" 15 CHARACTER location display
VISIBILITY:	125 Ft. (38.1 METERS)
POWER REQUIREMENTS:	100-240vac 50~60Hz (12 vdc SWITCHING TRANSFORMER).
FRAME:	ALUMINUM (BLACK ANODIZED FINISH)
DIMENSIONS:	10.25" x 76.25" x 1.38"
WEIGHT:	11.5 lbs.
OPERATING TEMP.:	-17° TO 190° F
HUMIDITY:	0% TO 95% NON-CONDENSING
OPERATING MODE:	31 DAY LIGHT SAVINGS, 31TIME ZONES, 10yr BATTERY BACKUP WITH 1sec A YEAR ACCURACY,
NON-GLARE LENS, EYELET AND SAW TOOTH SURFACE MOUNT, PC INTERFACE WITH DDS TimeNet 2.11 SOFTWARE INCLUDED.	


ALL CLOCKS USE THE DALLAS DS32 SERIES RTC PARTS, AND OUR FIRMWARE CONTROL, TO GET THE ONE SEC A YEAR ACCURACY.




1 SEC A YEAR ACCURATE (TCXO)



THE PC IS USED TO SET THE LOCATION DISPLAY AND TIME. THE CLOCK CAN RUN ON ITS OWN WITHOUT THE PC.





MOUNTING





**RS-232 SERIAL
PORT**

**DB9
CONNECTOR
SUPPLIED**



**RS-232
NOT OVER
100ft**

(+) SIDE
BLUE / WHITE
ORANGE / WHITE

For all system wiring
uses Wire-Nuts
SIZE 72B

(-) SIDE
WHITE / BLUE
WHITE / ORANGE

**ALL CLOCKS USE THE
DALLAS DS32 SERIES
RTC PARTS, AND OUR
FIRMWARE CONTROL,
TO GET THE ONE SEC
A YEAR ACCURACY.**



1 SEC A YEAR ACCURATE (TCXO)

GROUP CLOCK NUMBERS

0

1

2

3

12:18

CALIFORNIA

21:18

FRANKFURT

09:18

NEW ZEALAND

15:18

WASHINGTON D.C